



# Spectro UV-VIS Double Beam PC Scanning Spectrophotometer

**Model UVD-2960**



**NEW!**

Spectro UV-Vis Double PC (Model UVD-2960) is a high performance UV-Vis double beam automatic scanning spectrophotometer. It is a two (2) cell spectrophotometer with a variable bandwidth of 0.5, 1.0, 2.0 and 5.0 nm. Model UVD-2960 spectrophotometer offers high performance, ease of use and reliability, which can be used in various applications. Spectrophotometer Model UVD-2960 can be used extensively for qualitative and quantitative analysis in such fields as pharmaceutical inspection, clinical analysis, petro-chemistry laboratories, chemistry and biochemistry laboratories, DNA/RNA analysis as well as in quality control departments, i.e. environmental control, water management, food processing, and agriculture. Spectro UV-Vis Double PC utilizes a new optical system design and is microcomputer controlled. With its **focused-beam design**, the system provides optimal and reproducible results for small samples. The sample beam and the reference beam are provided within the same sampling space which in turn facilitates wider and longer scan of data providing a more detailed view of the results in an easy to use environment. This instrument has excellent baseline stability and high resolution and permits scanning, quantitative analysis, kinetic spectrophotometric analysis and DNA/RNA analysis through PC control. This product is capable of processing data, from analytical and spectrum testing.

Spectro UV-Vis Double PC (Model UVD-2960) has a large **LCD screen** which displays the menu screen and of course makes the device user-friendly. Additionally, this instrument has a powerful built-in software which permits the apparatus to be linked to a computer and a printer to display the photometric and spectral data on the PC monitor.

Spectro UV-Vis Double PC with variable bandwidth of 0.5, 1.0, 2.0 and 5.0nm. is a **high-performance, reliable, and exceptional value instrument** which is the hallmark of Labomed UV-Vis spectrophotometers.

**OUR NEW SOFTWARE UV-WIN 6.0 WITH 3D SPECTRA** Now all Labomed, Inc. split and double beam spectrophotometers with our newly developed software called UV-Win 6.0 can be used with Windows XP, Windows 7 and Windows 8. It is capable of testing more applications with its RS-232 and USB connections, and supports the data export of measured results to the PC and then, if required, a USB flash drive, when additional data storage is required. One of the new features is that it provides 3-D graphing of the spectral results.

Labomed, Inc. is certified by ISO-9001-2008, has CE Conformity and is FDA Licensed.

## Features

- **Baseline Stability:** The Double beam monitoring ratio system enhances baseline stability.
- **Excellent Resolution:** The big-caliber light path enhances the instrument's energy, reduces its noise and raises its resolution performance
- **2 Cell Holder:** Spectro UVD-2960 has 2 cell holder for reference (standard) and sample.
- **User-friendly light source:** The socket deuterium lamps and tungsten lamps facilitate light source replacement, simplify maintenance and reduce operation error.
- **Convenient Display:** The large backlit LCD screen displays both photometric values and spectral curves.
- **Full use of Computer Technology:** Being computer controlled with RS-232 and USB interface and working on the Windows platform with the UV/Win application software.
- The key components adopt all from the world famous manufacturer, such as deuterium lamp, silicon photodiode and holographic grating, which ensures the stabilization and credibility of the Instrument for extended life.
- **Computer System is optional (NOT INCLUDED).**

## Accessories

2 Fixed Cell Holder (one reference and one sample)  
8 Optical Glass Cells 10mm  
2 Quartz Cells 10mm  
1 Dust cover  
1 Instruction manual

1 Power cable  
1 PC cable  
1 Software CD for Windows 98/2000/XP  
1 Software Operation Manual

1 Block Light Cell  
1 Extra fuse  
**Optional:** Peltier Kinetic Test System  
**Optional:** Sipper Flow Through System