



LB-867 Trinocular Stereo Zoom Gemological Microscope with Extra Wide Field, 3.2MP Digital Camera, LED, Halogen and Fluorescent Illumination

Introduction

LB-867 Trinocular Stereo Zoom Gemological Microscope with Extra Wide Field, 3.2MP Digital Camera, LED, Halogen and Fluorescent Illumination is the microscope used by jewelers and gem stone experts, the gemological microscope is the most important tool in their jobs. LB-867 Trinocular Stereo Zoom Gemological Microscope with Extra Wide Field, 3.2MP Digital Camera, LED, Halogen and Fluorescent Illumination is especially designed to view precious stone samples and the pieces of jewelry that contain them. This microscope is equipped with multiple illumination systems to enhance the image of the sample.

Applications

LB-867 Trinocular Stereo Zoom Gemological Microscope with Extra Wide Field, 3.2MP Digital Camera, LED, Halogen and Fluorescent Illumination is usually used to inspect the authenticity of gemstones and in the design, creation, and repair of jewelry. It can be used for inspecting diamonds, emeralds, rubies, and all other types of precious stones.

Technical Specifications

Stereo Zoom Body: Zoom ratio $0.8 \times -4.5 \times$, zoom ratio 1:6.3, working distance 115mm Extra wide field eyepiece WF15 \times /22 with diopter adjustment

Binocular Digital Head: Built-in 3.2MP(2048*1536) digital camera. USB2.0 output. Digital Viewing Head,

Inclined at 45°, Interpupillary Distance 52-75mm

Bright & Dark Field Illumination: Iris diaphragm 2mm-41mm, Bright and dark viewing field illumination are adjustable

Illumination: 7W Fluorescent lamp(6000K)

LED Point Light

6V/20W Halogen illumination, lamp can be changed

Focusing: Focusing range: 100mm, it is suitable for observing different size gem and sample

Gem Clamp: High quality steel clamp is perfect to hold the gem for observation from all directions

Stage: At both side, there are two gem clamp fixing holds for you to choose

Stand: 0-38°Rotatable, so the height and angle of eyepiece can be adjusted, easy to operate

Base: 0-325° Rotatable

